

**PERFORMANCE**

	<u>English</u>	<u>SI</u>	
Stroke	0.4 in pk-pk	10 mm pk-pk	
Frequency Range, frequency response testing	2 to 20000 Hz	2 to 20000 Hz	
Frequency Range, resonant search testing	Up to 50 kHz	Up to 50 kHz	
Acceleration Level (sinusoidal)			
Continuous (25 to 10000 Hz)	8.5 g pk	83 m/s <sup>2</sup> pk	
Intermittent (35 to 10000 Hz)	40 g pk	392 m/s <sup>2</sup> pk	
Maximum Payload	17.6 oz	500 gm	[1]
Lifting Spring	Lorentz – force coil	Lorentz – force coil	
Air Supply Specifications			
Pressure	30 to 60 psi	2 to 4 bar	
Recommended flow supply to regulator	1.5 ft <sup>3</sup> /min	0.7 L/s	
Air-bearing flow rate (typical)	0.15-0.20 ft <sup>3</sup> /min	0.07-0.09 L/s	
ISO 8573.1 Quality	Class 3	Class 3	
Armature	Beryllium	Beryllium	
Insert	Beryllium	Beryllium	
Total mass	2.2 oz	62 gm	[2]
Sensor mounting thread size	¼-28 UNF	¼-28 UNF	[3]
Transverse Motion			[4]
<921Hz	5%	5%	[4]
<15000 Hz	10%	10%	[4]
<20000 Hz	20%	20%	[4]
Shaker Dimensions	6.5 x 5.25 inch	165 x 133 mm	
Shaker Weight	22.3 lbs	10.1 kg	

**System Components**

- 396C11: Air bearing shaker
- 080A200: Beryllium insert (1/4-28 mount) with internal reference accelerometer [2]
- 482A21: ICP® sensor signal conditioner
- 2100E23-C: SmartAmp™ AC power amplifier with integrated DC supply and air regulator
- 003C10: Reference accelerometer sensor cable
- 012A03: Signal conditioner output cable
- 012A01 (Qty 2): Shaker cable

**Included Accessories**

- Air filter assembly, includes filter and appropriate couplings
- Sensor mounting adapter kit, includes typical mounting adaptor studs and plates
- Primary calibration of internal reference accelerometer via laser interferometer for ultra low certainty of 0.2% at 100 Hz and 159 Hz
- Rack mount brackets for 2100E21 SmartAmp
- Power cables
- Spare fuses

**ELECTRICAL**

Drive-Coil Resistance	1.0 Ohm (nominal)	1.0 Ohm (nominal)
Lorentz-Coil Resistance	2.8 Ohm (nominal)	2.8 Ohm (nominal)

**INTERNAL REFERENCE ACCELEROMETER**

Type	Quartz Shear ICP®	Quartz Shear ICP®
Sensitivity	10 mV/g	1.02 mV/m/s <sup>2</sup>
Frequency Range (+/- 3dB)	0.35 to 30000 Hz	0.35 to 30000 Hz
Resonant Frequency	>70 kHz	>70 kHz

**POWER AMPLIFIER**

Output Voltage, max	38 V rms	38 V rms	[5]
Current Limit	18 A peak	18 A peak	[6]
Output Power	400 W	400 W	[7]
DC Current Supply	1.75 Amp	1.75 Amp	

*All specifications are at room temperature unless otherwise specified.*

**NOTES:**

- [1] DC coil payload limit. See manual for dynamic frequency response limits.
- [2] 080A200 is standard armature insert supplied. Other units available include 080A199 (10-32 thread), 080A205 (M6 x 0.75 – 6H thread), and 080A206 (M8 x 1.0 – 6H thread).
- [3] Typical, tested to ISO 16063-21:2003 recommendations.
- [4] These are typical values. TMS performs 100% acceptance testing to the suggested specifications of ISO 16063-21-2003.
- [5] At 4 Ω load impedance, 1 kHz, THD 0.1%.
- [6] Typical, over-current protection limited.
- [7] At 4 Ω load impedance, 1 kHz, THD 0.6%.

ICP® is a registered trademark of PCB Piezotronics, Inc.

*In the interest of constant product improvement, specifications may change without notice.*

Project Engineer: <b>NEW</b>	Product Manager: <b>CGK</b>	Mkt Team Leader: <b>DEG</b>	Spec Number: <b>PS-0092</b>
Date: <b>1/14/25</b>	Date: <b>1/14/25</b>	Date: <b>1/14/25</b>	